

DS-KD7003EY-IME2

HIKVISION INTERCOM



Features

- Hikvision
- Video door entry 2 HD wires with 2 Mpx camera
- Wide angle lens
- Built-in speaker and microphone
- IR night vision
- Remote monitoring via Hik-Connect mobile APP or indoor monitor
- Remote door opening
- Can be integrated with Hikvision modules
- Call status LED
- Surface mount or flush mount with bracket (not included)
- Retro-illuminated name tag
- Suitable for exterior IP65
- Anti-vandalism stainless steel surface IK08

Specifications

Brand	Hikvision
Model	DS-KD7003EY-IME2
Operating system	Linux
Image sensor	Low Illumination 2 Mpx IR
Image Functions	BLC / WDR / DNR
Viewing angle	H: 133°, V: 82°
Audio	Bidirectional audio with microphone and speaker
Keypad	1, 2 or no mechanical call button with LED customization label (customizable by means of included caps)
Outputs	2 x locking relay (1 with DC 12 V / 500 mA), 1 x module output
Inputs	2 x auxiliary inputs (exit button, door sensor), 1 x tamper
Remote access	Hik-Connect mobile application WiFi AP mode for configuration
Network interface	Network connection through 2 HD threads
Modular	Compatible with Hikvision modular boards
Power	DC 48 V with hub 2 HD wires DS-KAD7060EY / 12 V / 1700 mA max.
Degree of protection	Suitable for exterior IP65 Anti-vandal IK08
Material	Plastic and stainless steel
Temp. operation	-40° C ~ +60° C
Dimensions	98 (H) x 100 (W) x 35 (D) mm
Weight	290 g